




Permit drawings have been reviewed for architectural items related to the addition/renovations planned for the Rye Town Hall. I am familiar with the pertinent building and life safety code requirements utilized by the Town of Rye for projects of this type and size, and to the best of my knowledge these plans comply with the requirements laid out in the International Building Code 2015 and the NFPA 101-2015 Life Safety Code. This review does not include work related to other commonly required, and professionally licensed, disciplines related to commercial design and construction – Geotech, structural, civil, fire protection, and MEP engineering. For information regarding these specialties please refer to any drawings and specifications provided by the pertinent party.




REAR ELEVATION



FRONT ELEVATION



RIGHT ELEVATION



LEFT ELEVATION

| CODE REVIEW: IBC 2015 + NFPA 101-2015          |  |
|--|--|
| BASEMENT GROSS AREA                            | 557 SF   |
| FIRST FLOOR GROSS AREA                         | 2,961 SF (PHASE I: 2,255 SF EXISTING + 72 SF NEW / PHASE II: 634 SF NEW)             |
| TOTAL GROSS AREA                               | 3,518 SF   |
| PERIMETER                                      | 272'-3"  |
| NUMBER OF STORIES ABOVE GRADE                  | ONE STORY  |
| BUILDING HEIGHT                                | 16'-6"   |
| CONSTRUCTION TYPE                              | TYPE 5B (SECTION 602.5, IBC 2015)  |
| SPRINKLER SYSTEM                               | REQ. NO / PROVIDED: YES (SECTION 903.2.2, IBC 2015) (CHAPTER 38, NFPA 101)           |
| OCCUPANCY USE GROUP                            | (B) BUSINESS + (S-2) STORAGE (CHAPTER 3, IBC 2015)                                   |
| SEPARATED USE                                  | (B) REQUIRES 1HR SEPARATION FROM (S-2) (TABLE 508.4, IBC 2015)                       |
| <b>HEIGHT AND AREA LIMITATIONS</b>             |  |
| BASIC HEIGHT LIMITATIONS                       | 3 STORIES / 60'-0" (TABLE 504.3/504.4, IBC 2015)                                     |
| BASIC AREA LIMITATIONS                         | B - 27,000 SF (TABLE 506.2, IBC 2015)  |
| ELEVATOR REQUIRED                              | NO (SECTION 1104, IBC 2015)  |
| <b>MEANS OF EGRESS REQUIREMENTS (NFPA 101)</b> |  |
| OCCUPANT LOAD                                  | BASEMENT: (S-2) 557 SF/500 = 1   |
| TOTAL BUILDING OCCUPANT LOAD                   | 1ST FLOOR: (B) 2,961 SF/100 = 29   |
| MINIMUM NUMBER OF EXITS - (B) BUSINESS         | 30 PERSONS (TABLE 7.3.1.2, NFPA 101)   |
| MINIMUM NUMBER OF EXITS - (S-2) STORAGE        | 2 PER STORY / 2 PROVIDED (38.2.4.1(2), NFPA 101)                                     |
| REQUIRED CLEAR EGRESS WIDTH AT DOORS           | 1 PER STORY / 2 PROVIDED (42.2.4.1(2), NFPA 101) + PER AGREEMENT W/RYE DBI           |
| REQUIRED CLEAR EGRESS WIDTH AT STAIR           | 32" MIN. / 32" MIN. PROVIDED (7.2.1.2.3, NFPA 101)                                   |
| MAXIMUM DEAD END CORRIDOR                      | 36" MIN. / 44" MIN. PROVIDED (7.2.2.1.2(A), NFPA 101)                                |
| MAXIMUM COMMON PATH OF TRAVEL                  | (B) 50'-0" MAX and (S-2) 100'-0" MAX / 39'-9" MAX PROVIDED (TABLE A.7.6, NFPA 101)   |
| MAXIMUM TRAVEL DISTANCE                        | (B) 100'-0" MAX and (S-2) 100'-0" MAX / 60'-0" MAX PROVIDED (TABLE A.7.6, NFPA 101)  |
| MINIMUM CORRIDOR WIDTH                         | (B) 300'-0" MAX and (S-2) 400'-0" MAX / 77'-0" MAX PROVIDED (TABLE A.7.6, NFPA 101)  |
| <b>MEANS OF EGRESS REQUIREMENTS (IBC 2015)</b> |  |
| OCCUPANT LOAD                                  | BASEMENT: (S-2) 557 SF/300 = 1   |
| TOTAL BUILDING OCCUPANT LOAD                   | 1ST FLOOR: (B) 2,961 SF/100 = 29   |
| MINIMUM NUMBER OF EXITS - (B) BUSINESS         | 30 PERSONS (TABLE 1004.1.2, IBC 2015)  |
| MINIMUM NUMBER OF EXITS - (S-2) STORAGE        | 1 PER STORY / 2 PROVIDED (TABLE 1006.2.1, IBC 2015) + PER AGREEMENT W/RYE DBI        |
| REQUIRED CLEAR EGRESS WIDTH AT DOORS           | 32" MIN. / 32" MIN. PROVIDED (1010.1.1, IBC 2015)                                    |
| REQUIRED CLEAR EGRESS WIDTH AT STAIR           | 36" MIN. / 44" MIN. PROVIDED (1011.2.1, IBC 2015)                                    |
| MAXIMUM DEAD END CORRIDOR                      | (B) 50'-0" MAX and (S-2) 60'-0" MAX / 39'-9" MAX PROVIDED (1020.4.2, IBC 2015)       |
| MAXIMUM COMMON PATH OF TRAVEL                  | (B) 100'-0" MAX and (S-2) 100'-0" MAX / 60'-0" MAX PROVIDED (1006.2.1, IBC 2015)     |
| MAXIMUM TRAVEL DISTANCE                        | (B) 300'-0" MAX and (S-2) 400'-0" MAX / 77'-0" MAX PROVIDED (TABLE 1017.2, IBC 2015) |
| MINIMUM CORRIDOR WIDTH                         | 36" / 48" MIN. PROVIDED (1020.2, IBC 2015)   |
| EGRESS THROUGH INTERVENING SPACE               | ROOM 105 COMPLIES (1016.2.2, IBC 2015)   |
| <b>FIRE RATINGS</b>                            |  |
| EXTERIOR BEARING WALLS                         | TYPE 5B CONSTRUCTION   |
| INTERIOR BEARING WALLS                         | 0 HOUR (TABLE 601, IBC 2015)   |
| NON-BEARING INTERIOR WALLS                     | 0 HOUR (TABLE 601, IBC 2015)   |
| FLOOR CONSTRUCTION                             | 0 HOUR (TABLE 601, IBC 2015)   |
| ROOF CONSTRUCTION                              | 0 HOUR (TABLE 601, IBC 2015)   |
| STRUCTURAL FRAME                               | 0 HOUR (TABLE 601, IBC 2015)   |
| SHAFT ENCLOSURES                               | 1 HOUR (TABLE 713.4, IBC 2015)   |
| CORRIDOR SEPARATION                            | 0 HOUR (TABLE 1020.1, IBC 2015)  |
| HORIZONTAL SEPARATION                          | 1 HOUR BETWEEN (B) / (S-2) (SECTION 711.2.4.1, IBC 2025)                             |
| <b>REQUIRED PLUMBING FIXTURES</b>              |  |
| WATER CLOSETS                                  | (TABLE 2902.1, IBC 2015)   |
| LAVATORIES                                     | 1 PER 25 / 2 PROVIDED  |
| DRINKING FOUNTAIN                              | 1 PER 40 / 2 PROVIDED  |
| SERVICE SINK                                   | 1 PER 100 / 1 PROVIDED   |
| <b>ENERGY CODE - ENVELOPE REQUIREMENTS</b>     |  |
| ROOF   | (TABLE C402.1.3, IECC 2015)  |
| EXTERIOR WALL                                  | R-38   |
| BELOW GRADE WALL                               | R-20   |
| FLOOR  | R-7.5  |
| SLAB ON GRADE FLOOR                            | R-30   |
|  | R-10 FOR 24"   |

## INDEX

- A-0 COVER SHEET
- A-1 PHASE ONE & TWO ELEVATIONS
- A-2 PHASE ONE & TWO ELEVATIONS
- A-3 PHASE ONE & TWO PLAN
- A-4 PHASE ONE & TWO SECTION DETAILS
- A-5 PHASE ONE & TWO SECTION DETAILS
- A-6 PHASE ONE & TWO SECTION DETAILS
- A-7 PHASE ONE & TWO LOBBY ELEVATIONS
- A-8 PHASE ONE & TWO INTERIOR ELEVATIONS
- A-9 PHASE ONE & TWO ROOM / WINDOW SCHEDULES
- A-10 PHASE ONE & TWO REFLECTED CEILING PLAN
- A-11 PHASE ONE & TWO ELECTRICAL AND PLUMBING PLAN
- ROSS ENGINEERING COVER SHEET
- S-1 FOUNDATION PLAN
- S-2 PROPOSED FRAMING
- S-3 DETAILS
- S-4 PROPOSED ROOF FRAMING
- S-5 NOTES
- D-1 DEMOLITION FLOOR PLAN
- D-2 DEMOLITION ELEVATIONS
- D-3 DEMOLITION ELEVATIONS
- E-1 EXISTING PLAN
- E-2 EXISTING ELEVATIONS
- E-3 EXISTING ELEVATIONS

## GENERAL SPECIFICATIONS

1. WORK INCLUDED IN THIS CONTRACT SHALL CONFORM TO THE STATE, NATIONAL, AND OTHER CODES AND ORDINANCES THAT APPLY TO THIS PROJECT.
2. BRING ANY DISCREPANCIES IN THESE PLANS TO THE ARCHITECT'S ATTENTION IMMEDIATELY.
3. REFER TO MECHANICAL, ELECTRICAL, PLUMBING AND FIRE PROTECTION DRAWINGS AND SPECIFICATIONS FOR LOCATIONS OF ALL BLOCK OUTS, INSERTS, OPENINGS, CURBS, BASES, AND PADS THAT ARE NOT DIMENSIONED OR SHOWN ON ARCHITECTURAL OF STRUCTURAL DRAWINGS, TYP.
4. STRUCTURAL, MECHANICAL, ELECTRICAL, PLUMBING, AND FIRE PROTECTION DRAWINGS AND SPECIFICATIONS SHALL BE PROVIDED AND ARE THE RESPONSIBILITY OF THEIR RESPECTIVE SUBCONTRACTORS AND THEIR DESIGN BUILD ENGINEER.
5. THE LOCATION OF DOOR OPENINGS NOT DIMENSIONED SHALL BE 6" FROM ADJACENT WALL (FACE OF FRAMING TO ROUGH OPENING).
6. PERMITS ARE THE RESPONSIBILITY OF THE CONTRACTOR AND SHALL BE COORDINATED WITH PHASING AND WITH THE LOCAL BUILDING COMMISSIONER.
7. WORK SHALL BE COMPLETED IN COMPLIANCE WITH INDUSTRY STANDARDS
8. RATED WALL SYSTEMS TO HAVE CONTINUOUS SEALANT AT BASE AND TOP OF WALL.
9. PROVIDE 5/8" TYPE 'X' GYPSUM BOARD AT RATED WALL PARTITIONS.
10. PROVIDE 5/8" MOISTURE RESISTANT (MR) GYPSUM BOARD IN TOILET ROOMS.
11. PROVIDE FIRESTOPPING AT PENETRATIONS IN FIRE RATED WALLS AND FLOORS. PROVIDE FIRESTOPPING WHERE FIRE RATED ASSEMBLIES ABOUT OTHER CONSTRUCTION.
12. PENETRATIONS IN FIRE RESISTANCE RATED ASSEMBLIES SHALL BE PROTECTED BY AN APPROVED PENETRATION FIRESTOP SYSTEM INSTALLED AS TESTED IN ACCORDANCE WITH ASTM E814 OR UL 1479.
13. GC TO ENSURE ALIGNMENT OF ALL NEW AND EXISTING WALL AND FLOOR ASSEMBLIES.
14. HANDRAILS COMPLYING WITH IBC 2015 DIMENSIONAL STANDARDS ARE REQUIRED ON BOTH SIDES OF STAIRS.
15. SPRINKLER ROOM LAYOUT AND ACCESS SHALL NOT CONFLICT WITH ADA CLEAR SPACE REQUIREMENTS IN BATHROOM.
16. VAULT CONSTRUCTION: BASIS OF DESIGN - STANDARD FOR FIRE-RESISTIVE VAULTS AND SAFES - CONNECTICUT STATE AGENCIES STATE LIBRARY.
17. CARRY ADEQUATE WORKMAN'S COMPENSATION AND LIABILITY INSURANCE FOR

- PERFORMANCE OF THE WORK.
18. INDEMNIFY AND HOLD HARMLESS THE OWNER AND ARCHITECT FROM ALL CLAIMS AND EXPENSES FOR BODILY INJURY AND PROPERTY DAMAGE CAUSED BY THE NEGLIGENCE OR OMISSION OF THE CONTRACTOR OR HIS WORKS OR SUBCONTRACTORS.
19. SECURE ALL PERMITS AS REQUIRED TO PERFORM THE WORK.
20. DISPOSE OF ALL RUBBISH AND LEAVE THE PREMISES "BROOM CLEAN."
21. PERFORM ALL WORK IN A NEAT AND WORKMANLIKE MANNER ACCORDING TO ACCEPTED PRACTICES AND STANDARDS SPECIFIC TO EACH TRADE. ALL WORK SHALL STRICTLY COMPLY WITH THE CONSTRUCTION DRAWINGS, SPECIFICATIONS, AND APPLICABLE LAWS AND CODES.
22. BREAKOUT COST FOR PHASE 1 AND PHASE 2. ANY DISCREPANCIES GO TO COST FOR PHASE 1.
23. FIELD VERIFY ALL MEASUREMENTS AND CONDITIONS AND NOTIFY THE OWNER OF ANY DISCREPANCIES OR CIRCUMSTANCES THAT AFFECT THE WORK.
24. GUARANTEE THE WORK TO BE FREE OF DEFECTS IN MATERIALS AND WORKMANSHIP FOR A PERIOD OF ONE YEAR AFTER COMPLETION, ROOFING FOR 10 YEARS. SHOULD A DEFECT ARISE, THE OWNER SHALL NOTIFY THE CONTRACTOR IMMEDIATELY AND THE CONTRACTOR SHALL HAVE A WORKER ON THE JOB, ACTING TO CORRECT THE DEFECT, WITHIN ONE WEEK'S TIME. SHOULD THE CONTRACTOR DEFAULT TO THIS CONDITION, THE OWNER MAY HIMSELF ACT TO CORRECT THE DEFECT AND BE COMPENSATED BY THE CONTRACTOR FOR EXPENSES INCURRED.
25. CHANGE ORDERS - THE OWNER RESERVES THE RIGHT TO PERFORM CHANGES IN THE WORK.
26. MECHANICAL, ELECTRICAL, PLUMBING, AND SPRINKLER SYSTEM WORK TO BE CARRIED OUT BY LICENSED TRADES PEOPLE. SHOP DRAWINGS TO BE PROVIDED BY CONTRACTOR PRIOR TO CONSTRUCTION.
27. CONTRACTORS BIDDING THIS JOB SHALL CARRY AN ALLOWANCE FOR A SPRINKLER SYSTEM. SEPARATE PHASE 1 AND PHASE 2 IN THE PRICING.
28. THE BUILDING HEATING AND COOLING SHOULD BE PROVIDED EITHER BY AN AIR TO AIR HEAT PUMP SYSTEM OR A HIGH EFFICIENCY PROPANE FURNACE AND AIR CONDITIONING SYSTEM. THE AIR TO AIR HEAT PUMP SHALL MEET OR EXCEED THE EFFICIENCY SPECIFICATIONS IN THE ATTACHED EVERSOURCE 2021 HVAC INCENTIVE APPLICATION. IF THE AIR TO AIR HEAT PUMP IS RECOMMENDED AND BACKUP HEAT IS RECOMMENDED, IT SHALL BE PROVIDED BY A PROPANE UNIT.


CONSTRUCTION SET

|   |   |
|---|---|
| <p><b>RYE TOWN OFFICE</b><br/>RYE, NH.</p>  | <p>COVER SHEET<br/>SCALE: 3/16"=1'-0"</p> |
| <p><b>CHARLES HOYT DESIGNS</b><br/>CHANGE STYLE ARCHITECTURE<br/>P.O. BOX 236<br/>RYE, NH 03071<br/>(603) 431-5310<br/>charles@hoyt-designs.com</p> | <p><b>A0</b></p>                          |


12-1-21



| LEGEND   |  |
|----------|--|
| EXISTING |  |
| DEMO.    |  |
| NEW      |  |



**PROPOSED PHASE ONE AND TWO ELEVATIONS**



|                                |   |  |
|--------------------------------|---|--|
| <p><b>CONSTRUCTION SET</b></p> | <p>RYE TOWN OFFICE<br/>RYE, NH.</p>   | <p>PHASE ONE &amp; TWO ELEVATIONS<br/>SCALE: 3/16"=1'-0"</p> |
|                                | <p>CHARLES<br/>HOYT<br/>DESIGNS<br/>Shingle Style Architecture<br/>P.O. BOX 236<br/>Bornton, NH 03311<br/>(603) 431-5310<br/>charles@hoymtdesigns.com</p> |  |
|                                |   | <p><b>A1</b></p> <p>12-1-21</p>                              |

PHASE TWO

- 1. ROOF SHINGLE: Landmark (Color; Country Grey)  
(by certainteed Triple Laminate HD Profile) (or approved equal)  
Roof: Asphalt 45 Year Shingle  
O/ ProArmor Underlayment By Owens Corning
- Grace Ice And Water Shield At Eaves And Valleys  
3' Up Eave W/ Copper Drip Edge.
- Roof Of Existing Building To Be Stripped Down To Existing Sheathing  
Remove All Underlayment, Drip Edge, Patch And Repair As Needed.

20. REPAIR EXISTING FASCIA TO MATCH  
INSPECT AND VERIFY EXTENT IN FIELD

PHASE ONE

- 2. TRIM: Corner Bds, Frieze, Fascia, Soffits, Window Trim, Columns, Etc. To Remain.  
Contractor To Clean and Paint White W/ Benjamin Moore Paint
- 3. WINDOW: Double Hung Wood W Composite Clad Exterior Sash Painted White
- 4. SHUTTERS: Composite Wood Shutters Flat Panels (Painted Black)  
By Atlantic From Broscos. (Or Equal) W/ Black Metal 'S' Shapped Hold Backs
- 5. SIDING : Existing To Remain, Clean, Patch , Repair & Paint (White) Benjamin Moore

PHASE TWO DEMO:

PHASE TWO  
NEW ROOF BEYOND

| LEGEND   |  |
|----------|--|
| EXISTING |  |
| DEMO.    |  |
| NEW      |  |

FRONT ELEVATION

PHASE TWO

- 7. ROOF SHINGLE: Landmark (Color; Country Grey)  
(by certainteed Triple Laminate HD Profile) (or approved equal)  
Roof: Asphalt 45 Year Shingle  
O/ 5/8" Roof Sheath. (Zip System)  
W/ Zip Tape @ All Joints (Typ.)  
O/ 2 x 10's @ 16" O.C. Filled W/ Min R-42  
Rigid. Insul. Hurricane Clips @ Wall @ Every Rafter (Typ.)
- Grace Ice And Water Shield At Eaves And Valleys  
3' Up Eave W/ Copper Drip Edge.

8. FASCIA: copper drip edge O/  
(5") Crown Moulding By Azek  
Model Number: AZM-47 (See Detail)

9. FRIEZE: Bed Moulding  
Model Number: AZM-75 O/ 5/4" x 10 Azek Trim.

10. SOFFIT: Vinyl Soffit By Certainteed

PHASE TWO

PHASE ONE

11 TRIM: Existing Wood Trim To Remain IE. Rakes, Crown Mouldings Etc...  
Contractor To Clean and Paint White W/ Benjamin Moore Paint  
(Color solid Ultra white 001)

14. SIDING : Remove Existing Siding and Sheathing  
Green Guard Or Equal Underlayment O/ New Sheathing  
WALL: White Cedar Shingle By Maybee (Color solid Ultra white 001)

FIRST FLOOR


16. EXISTING WINDOW TO REMAIN

17. RELOCATED NIGHT DEPOSITORY  
CUT AND FRAME NEW OPENING.  
FINISH TO MATCH

PHASE TWO

PHASE ONE


PROPOSED PHASE ONE AND TWO ELEVATIONS



CONSTRUCTION SET

|  |                  |
|--|------------------|
| <p><b>RYE TOWN OFFICE</b><br/>RYE, NH.</p>   |                  |
| <p>PHASE ONE &amp; TWO ELEVATIONS<br/>SCALE: 3/16"=1'-0"</p>   |                  |
| <p><b>CHARLES HOYT DESIGNS</b><br/>Shingle Style Architecture<br/>P.O. BOX 256<br/>Rye, NH 03071<br/>(603) 431-5310<br/>charles@hoyt-designs.com</p> | <p><b>A2</b></p> |
| <p>12-1-21</p>   |                  |





**LEGEND**

EXISTING

PHASE ONE

PHASE TWO

**NOTES:**

1. SOUND DEADENING INSULATION AT ALL RESTROOM WALLS

EXISTING BUILDING: 2,255 S.F.  
 PHASE ONE ADDITION: 72 S.F. (Gross Sq. Ft. Vault Rm.)  
 PHASE TWO ADDITION: 634 S.F.

**PROPOSED PHASE ONE AND TWO FLOOR PLAN**


**CONSTRUCTION SET**

**RYE TOWN OFFICE**  
 RYE, NH.

PHASE ONE & TWO PLAN  
 SCALE: 3/16"=1'-0"

**A3**


12-1-21




**CHARLES HOYT DESIGNS**  
 Single Style Architecture  
 P.O. BOX 236  
 RYE, NH 03071  
 (603) 431-5310  
 charles@hoytanddesign.com




ROOF SHINGLE: Landmark (Color; Country Grey)  
 (by certainteed Triple Laminate HD Profile) (or approved equal)  
 Roof: Asphalt 45 Year Shingle  
 O/ 5/8" Roof Sheath. (Zip System)  
 W/Zip Tape @ All Joints (Typ.)  
 O/ rafter's @ 16" O.C. Filled W/ Min R-42  
 Rigid.Insul. Hurricane Clips @ Wall @ Every Rafter (Typ.)  
 Grace Ice And Water Shield At Eaves And Valleys  
 3' Up Eave W/ Copper Drip Edge.




1. VAULT WALL SECTION



2. DOG HOUSE SECTION



3. BUSINESS OFFICE DESK




4. ASSESSOR'S OFFICE DESK

CONSTRUCTION SET

|  |  |  |
|--|--|--|
| RYE TOWN OFFICE<br>RYE, NH.  |  | PHASE ONE & TWO SECT. DETAILS<br>SCALE: 1"=1'-0" |
| CHARLES HOYT DESIGNS<br><small>Shingle Style Architecture</small><br>P.O. BOX 256<br>85 E. Beach, NH 03871<br>(603) 431-5310<br><a href="mailto:charleshoytdesigns@hotmail.com">charleshoytdesigns@hotmail.com</a> |  | <b>A4</b>  |
|  |  | <b>12-1-21</b>                                   |






### PROPOSED PHASE TWO SECTION A

Fastened W/ An Approved Connector,


INSULATION COMPLIANCE - R-21 MIN.



### PROPOSED PHASE TWO SECTION B





### NOTES:

9. Soil bearing capacity should be tested and rated for 3000 PSF
10. Footing should rest on undisturbed soils. If ledge is encountered footing should be pinned to rock w/ 1/2" long #5 rebar 6" into rock & 6" into footing @ 6' o.c.
11. Footing: 24" wide x 10" thick reinforced w/ 4 rows of #4 rebar continuous,
12. Pin wall to footing w/ #4 vertical rebar @ 24" O.C. Up 24" Into Wall (Typ.)  
Footings For Point Loads, Reinforce W Rows In Both Directions @ 12" o.c.  
Strip Footer: Reinforce W/ 4 Rows Of # 4 rebar continuous 3" up from bottom.
13. Foundation wall: 10" thick. Reinf. w/ #4 Rebar (1) Row 2" from Top, and (1) Row 2" from bottom  
Place Extra #4 Vertical Rebar Below Locations Where Post Sits on Foundation.
14. Pin P.T. Plate to foundation wall w/ 1/2" diameter x 1'-0" anchor bolts 4'-0" O.C. (Typ.)  
There shall be a minimum of two bolts per sill plate section and not more than 12" from each end.
15. 5" SHELF - SEE SECTIONS
16. CONTRACTOR TO CARRY 10% FOR UNKNOWNNS
17. ONE HOUR FIRE RATED FLOOR BETWEEN BASEMENT AND FIRST FLOOR
18. INSULATION: R-42 POLYURETHANE SPRAY AT ROOF, R-21 FIBERGLASS BATT INSULATION AT FLOOR AND EXTERIOR WALLS - UNLESS NOTED OTHERWISE



CONSTRUCTION SET

|  |   |
|--|---|
| <b>RYE TOWN OFFICE</b><br>RYE, NH.   | PHASE ONE & TWO SECT. / DET<br>SCALE: 3/16"=1'-0" |
| <b>CHARLES HOYT DESIGNS</b><br><small>Single Style Architecture</small><br>P.O. BOX 236<br>RYE, NH 03301<br>(603) 431-5310<br>charles@hoyt.com | <b>A5</b>   |
| 12-1-21  |   |



**CONSTRUCTION SET**

**RYE TOWN OFFICE**  
RYE, NH.


**CHARLES HOYT DESIGNS**  
Single Style Architecture  
P.O. BOX 256  
850 Rte. 101  
Rye, NH 03071  
603-431-5310  
charles@hoyt-designs.com

PHASE ONE & TWO SECT. / DET  
SCALE: 3/16"=1'-0"


**A6**

12-1-21






LOBBY ELEVATION - AT COUNTER




LOBBY ELEVATION - CORRIDOR BEYOND




TYPICAL LOBBY ELEVATION

**NOTES:**


- SOLID 2x8 BLOCKING IN WALL AND CEILINGS TO RECEIVE SHIPLAP OR BEADBOARD



3. BASEBOARD PROFILE  
1x8 SPEED BASE




2. CROWN MOULDING PROFILE




1. MOULDING PROFILE

CONSTRUCTION SET


|  |           |
|--|-----------|
| <b>RYE TOWN OFFICE</b><br>RYE, NH.   |           |
| PHASE ONE & TWO LOBBY ELEV<br>SCALE: 1/2"=1'-0"  |           |
| <b>CHARLES HOYT DESIGNS</b><br><small>Single Style Architecture</small><br>60 BOYD, 266<br>RYE, NH 03871<br>(603) 431-5310<br>charleshoymdesigns@hotmail.com | <b>A7</b> |
| <b>12-1-21</b>   |           |








RESTROOM ELEVATION



STAFF BREAK ROOM ELEVATION

**SPECIFICATIONS:**

1. TOILET: American Standard Cadet  
1.1 gpf Pressure Ass. Elongated Toilet (White)
2. SINK: American Standard Aqualyn  
Countertop Sink W/ 8" Faucet Holes (White Typ.)
3. FAUCET: American Standard Portsmouth Suite  
2 Handle 8" Widespread High Arc W/ Level Handles  
Finish: Polished Chrome (Typ.)
4. VANETY: Formica High Pressure Laminate  
Matte Finish Color: Creme Quarstone.  
O/ 3/4" Plywood. Support Top W/ Adequate Brackets  
(Three In Total, At Each End and At Mid Span).
5. TILE FLOOR: SEE ROOM FINISH SCHEDULE
6. TILE WALL: SEE ROOM FINISH SCHEDULE
7. GYPSUM BOARD WALL: 1/2" XP Purple Moisture Resistant Gypsum Board  
Painted W/ Benjamin Moore Paints Color: White Dove.
8. DOOR W/ TRIM: Solid Core Masonite Flush Door  
W/ 1 x 3 Colonial Trim (To Match Existing) Typ.
9. DOOR HARDWARE:  
ADA accessible door handles.
10. WALL STRUCTURAL:  
Solid Blocking At Grab Bars, Paper Towel Dispensers,  
Toilet Paper Dispenser, and all wall mounted fixtures



CONSTRUCTION SET


|  |   |   |
|--|---|---|
| <b>CHARLES HOYT DESIGNS</b><br><small>Single Style Architecture</small><br>10 BOYD, 216<br>Rye Beach, NH 03871<br>(603) 431-5310<br><a href="mailto:charleshoymtdesigns@hotmail.com">charleshoymtdesigns@hotmail.com</a> | <b>RYE TOWN OFFICE</b><br><b>RYE, NH.</b> | <b>PHASE ONE &amp; TWO INT. ELEV.</b><br><b>SCALE: 1/2"=1'-0"</b> |
| <b>12-1-21</b>   |   | <b>A8</b>   |



| ROOM FINISH SCHEDULE   |                        |  |   |  |                                     |                                 |
|--|------------------------|--|---|--|-------------------------------------|---------------------------------|
| PHASE ONE  |                        |  |   |  |                                     |                                 |
| ROOM NUMBER  | ROOM NAME              | FLOOR  | WALL  | CEILING  | MOLDINGS                            | NOTES                           |
| 100  | VESTIBULE              | PERGO DEFENSE+ 7.5" W BANFIELD BRIDGE OAK ANTIMICROBIAL                        | 7/16" x 7 1/2" SHIPLAP                      | BEADBOARD CEILING 7/16" V GROOVE PANEL                       | 4" PINE CROWN                       |                                 |
| 101  | LOBBY                  | PERGO DEFENSE+ 7.5" W BANFIELD BRIDGE OAK ANTIMICROBIAL                        | 7/16" x 7 1/2" SHIPLAP                      | BEADBOARD CEILING 7/16" V GROOVE PANEL                       | 4" PINE CROWN                       | SEE SHEET A7 DETAIL SHEET       |
| 102  | TAX ASSESSOR'S OFFICE  | TRAFFICMASTER GRAND FORKS GRAY COMMERCIAL CARPET W/ 5/16" CUSHION BY LIFEPROOF | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE |                                 |
| 103  | TOWN'S BUSINESS OFFICE | TRAFFICMASTER GRAND FORKS GRAY COMMERCIAL CARPET W/ 5/16" CUSHION BY LIFEPROOF | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE |                                 |
| 104  | VAULT ROOM             | PERGO DEFENSE+ 7.5" W BANFIELD BRIDGE OAK ANTIMICROBIAL                        | PAINTED GWB SMOOTH                          | PAINTED GWB SMOOTH   | ROPPE BLACK 4" VINYL WALL COVE BASE | 1 HOUR FIRE RATED VAULT ROOM    |
| 105  | TOWN CLERK'S OFFICE    | TRAFFICMASTER GRAND FORKS GRAY COMMERCIAL CARPET W/ 5/16" CUSHION BY LIFEPROOF | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE |                                 |
| 106  | TREASURER'S OFFICE     | TRAFFICMASTER GRAND FORKS GRAY COMMERCIAL CARPET W/ 5/16" CUSHION BY LIFEPROOF | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE |                                 |
| 107  | MAIL / COPY            | 12"x12" ARMSTRONG IMPERIAL TEXTURE COMMERCIAL VCT                              | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE |                                 |
| 108  | CORRIDOR               | 12"x12" ARMSTRONG IMPERIAL TEXTURE COMMERCIAL VCT                              | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE |                                 |
| 109  | CONFERENCE ROOM        | TRAFFICMASTER GRAND FORKS GRAY COMMERCIAL CARPET W/ 5/16" CUSHION BY LIFEPROOF | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE |                                 |
| 110  | MEN'S RESTROOM         | CARRARA 12" x 24" POLISHED PORCELAIN FLOOR AND WALL TILE - POLISHED WHITE      | PAINTED GWB SMOOTH WALL TILE TO MATCH FLOOR | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS |                                     | SEE SHEET A10 ELEVATIONS        |
| 111  | WOMEN'S RESTROOM       | CARRARA 12" x 24" POLISHED PORCELAIN FLOOR AND WALL TILE - POLISHED WHITE      | PAINTED GWB SMOOTH WALL TILE TO MATCH FLOOR | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS |                                     | SEE SHEET A10 ELEVATIONS        |
| 112  | STAFF BREAK ROOM       | 12"x12" ARMSTRONG IMPERIAL TEXTURE COMMERCIAL VCT                              | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE |                                 |
| 113  | UTILITY ROOM           | 12"x12" ARMSTRONG IMPERIAL TEXTURE COMMERCIAL VCT                              | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE |                                 |
| PHASE TWO  |                        |  |   |  |                                     |                                 |
| ROOM NUMBER  | ROOM NAME              | FLOOR  | WALL  | CEILING  | MOLDINGS                            | NOTES                           |
| 200  | CORRIDOR               | 12"x12" ARMSTRONG IMPERIAL TEXTURE COMMERCIAL VCT                              | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE |                                 |
| 201  | OFFICE                 | TRAFFICMASTER GRAND FORKS GRAY COMMERCIAL CARPET W/ 5/16" CUSHION BY LIFEPROOF | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE | CLOSET FINISHES TO MATCH OFFICE |
| 202  | OFFICE                 | TRAFFICMASTER GRAND FORKS GRAY COMMERCIAL CARPET W/ 5/16" CUSHION BY LIFEPROOF | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE | CLOSET FINISHES TO MATCH OFFICE |
| 203  | OFFICE                 | TRAFFICMASTER GRAND FORKS GRAY COMMERCIAL CARPET W/ 5/16" CUSHION BY LIFEPROOF | PAINTED GWB SMOOTH                          | 24" x 48" RADAR WHITE SQUARE EDGE LAY-IN ACT BY USG CEILINGS | ROPPE BLACK 4" VINYL WALL COVE BASE | CLOSET FINISHES TO MATCH OFFICE |
| <b>NOTES</b><br>1. ALL PRODUCTS AS SPECIFIED, OR APPROVED EQUAL<br>2. SELF LEVELING LIGHT WEIGHT CONCRETE OR EQUAL ON ALL EXISTING FLOORS - 3/4" TO 1" THICK |                        |  |   |  |                                     |                                 |

| WINDOW SCHEDULE |                          |                   |  |
|-----------------|--------------------------|-------------------|--|
| TAG             | DESCRIPTION              | ROUGH OPENING     | NOTES                                    |
| A               | REPLACEMENT DOUBLEHUNG   | 38 5/8" x 53 3/8" | SEE LEPAGE MILLWORK CUT SHEET FOR SPECS. |
| B               | NEW DOUBLEHUNG           | 38 5/8" x 53 3/8" | SEE LEPAGE MILLWORK CUT SHEET FOR SPECS. |
| C               | 18" RADIUS CIRCLE WINDOW | 37" x 36 1/2"     | SEE LEPAGE MILLWORK CUT SHEET FOR SPECS. |
| D               | LEFT HINGED CASEMENT     | 33" x 54 1/2"     | SEE LEPAGE MILLWORK CUT SHEET FOR SPECS. |
| E               | RIGHT HINGED CASEMENT    | 33" x 54 1/2"     | SEE LEPAGE MILLWORK CUT SHEET FOR SPECS. |
| F               | NEW AWNING               | 25" x 24 1/2"     | SEE LEPAGE MILLWORK CUT SHEET FOR SPECS. |
| G               | BASEMENT                 | 33" x 24 1/2"     | BASEMENT UTILITY WINDOW                  |


| DOOR SCHEDULE |                       |                   |  |
|---------------|-----------------------|-------------------|--|
| TAG           | DESCRIPTION           | ROUGH OPENING     | NOTES  |
| 1             | FRONT DOOR            | 76 1/2" x 80 1/8" | SEE LEPAGE MILLWORK CUT SHEET FOR SPECS.   |
| 2             | FRONT DOOR            | 76 1/2" x 80 1/8" | SEE LEPAGE MILLWORK CUT SHEET FOR SPECS.   |
| 3             | REAR DOOR             | 38" x 82 1/2"     | SEE LEPAGE MILLWORK CUT SHEET FOR SPECS. DOOR NUMBER THREE FROM PHASE ONE TO BE RE-USED IN PHASE TWO |
| 4             | UTILITY ROOM          | 38" x 82 1/2"     |  |
| 5             | STAFF BREAK           | 38" x 82 1/2"     |  |
| 6             | WOMEN'S ROOM          | 38" x 82 1/2"     | ADA ACCESSIBLE   |
| 7             | MEN'S ROOM            | 38" x 82 1/2"     | ADA ACCESSIBLE   |
| 8             | CONFERENCE            | 38" x 82 1/2"     |  |
| 9             | SPRINKLER ROOM        | 38" x 82 1/2"     |  |
| 10            | TREASURER'S OFFICE    | 34" x 82 1/2"     |  |
| 11            | TREASURER'S OFFICE    | 34" x 82 1/2"     |  |
| 12            | TOWN CLERK            | 38" x 82 1/2"     |  |
| 13            | VAULT                 | 38" x 82 1/2"     | STEEL JAMB AND STEEL DOOR WITH SELF CLOSING HARDWARE ONE HOUR FIRE RATED                             |
| 14            | TAX ASSESSOR          | 34" x 82 1/2"     |  |
| 15            | BUSINESS OFFICE       | 38" x 82 1/2"     |  |
| 16            | TAX ACCESSOR          | 38" x 82 1/2"     |  |
| 17            | MAIL / COPY           | 38" x 82 1/2"     |  |
| 18            | ASSESS ASSIST. OFFICE | 34" x 82 1/2"     |  |
| 19            | OFFICE                | 38" x 82 1/2"     |  |
| 20            | CLOSET                | 32" x 82 1/2"     |  |
| 21            | OFFICE                | 38" x 82 1/2"     |  |
| 22            | CLOSET                | 32" x 82 1/2"     |  |
| 23            | OFFICE                | 38" x 82 1/2"     |  |
| 24            | CLOSET                | 32" x 82 1/2"     |  |



CONSTRUCTION SET

|  |   |                      |
|--|---|----------------------|
| <b>CHARLES HOYT DESIGNS</b><br>Architecture<br>P.O. BOX 236<br>Rye, NH 03071<br>(603) 431-5310<br>charlesoyt@charlesoytdesigns.com | <b>RYE TOWN OFFICE</b><br><b>RYE, NH.</b><br>PHASE ONE & TWO RM / WINDOW / DOOR SCHEDULES<br>SCALE: 3/16"=1'-0" | <b>A9</b><br>12-1-21 |
|--|---|----------------------|






| LEGEND |  |
|--------|--|
|        | LED RECESSED FIXTURE   |
|        | HISTORIC STYLE LED FIXTURE - TBD BY ARCHITECT / HISTORIC COMMITTEE |
|        | CEILING MOUNTED LED LIGHT FIXTURE                                  |
|        | LED LIGHT FIXTURE  |
|        | 2x4" LED TROFFER LIGHT FIXTURE                                     |
|        | LED EMERGENCY LIGHTING - BATTERY                                   |

**NOTES:**

1. ALL NEW DROP CEILINGS SHALL BE 8'-0" A.F.F.
2. STRAPPING IN CEILING: 2x8 STRUCTURAL CEILING 16" O.C. AT A HEIGHT OF 8'-9" +/-
3. SUSPENDED CEILING AREA IN EXCESS OF 1,000 S.F. SHALL HAVE LATERAL FORCE BRACING
4. ALL TRADES SHALL PARTICIPATE IN A COORDINATION MEETING PRIOR TO ANY INSTALLATION OF CEILING
5. ALL CEILING MOUNTED DEVICES, LIGHTS, HVAC GRILLES, ETC ARE TO BE CENTERED ON FULL PANELS IN ALL DIRECTIONS
6. FIELD VERIFY EXISTING STRUCTURAL CEILING TO DETERMINE IF IT CAN REMAIN
7. VERIFY ACCESS FOR NEW MECHANICAL EQUIPMENT IN ATTIC PRIOR TO CONSTRUCTION OF CEILING



|                         |   |  |
|-------------------------|---|--|
| <b>CONSTRUCTION SET</b> | <b>RYE TOWN OFFICE<br/>RYE, NH.</b>   | <b>PHASE ONE &amp; TWO REFLECTED<br/>CEILING PLAN<br/>SCALE: 3/16"=1'-0"</b> |
|                         | <b>CHARLES HOYT DESIGNS</b><br>Single Style Architecture<br>P.O. BOX 256<br>RYE, NH 03071<br>(603) 431-5310<br>charles@hoymtdesigns@hotmail.com |  |

**PROPOSED PHASE ONE & TWO REFLECTED CEILING PLAN**




**NOTES:**

1. CODES: ALL EQUIPMENT AND MATERIALS FURNISHED UNDER THE ELECTRICAL SUB CONTRACTS AND LABOR PERFORMED HEREIN SHALL BE IN COMPLETE ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, FIRE PROTECTION ASSOCIATION, AND INSURANCE REGULATIONS AND REQUIREMENTS GOVERNING SUCH WORK.
2. PERMITS: ANY AND ALL PERMITS REQUIRED FOR INSTALLATION OF ANY MATERIAL SHALL BE OBTAINED AS PART OF THE WORK OF THE SPECIFICATION INCLUDING ALL FEES OR EXPENSES INCURRED.
3. THE WORK COVERED CONSISTS OF FURNISHING ALL LABOR AND MATERIALS NECESSARY TO INSTALL, COMPLETE AND READY FOR CONTINUOUS OPERATION, THE ELECTRICAL SYSTEMS, APPARATUS AND EQUIPMENT FOR RYE TOWN HALL.
4. SHOP DRAWINGS OF ALL SPECIFIED FIXTURES, EQUIPMENT AND APPARATUS SHALL BE SUBMITTED TO THE ARCHITECT FOR APPROVAL.
5. CONTRACTOR TO FIELD VERIFY EXISTING UTILITIES AND CONDITIONS PRIOR TO SUBMITTING AS BID.
6. GUARANTEE: ALL MATERIALS AND EQUIPMENT, FURNISHED AND INSTALLED, SHALL BE GUARANTEED IN WRITING FOR (1) ONE YEAR, FROM THE DATE OF ACCEPTANCE OF THE BUILDING BY THE OWNER.
7. THE BUILDING HEATING AND COOLING SHOULD BE PROVIDED EITHER BY AN AIR TO AIR HEAT PUMP SYSTEM OR A HIGH EFFICIENCY PROPANE FURNACE AND AIR CONDITIONING SYSTEM. THE AIR TO AIR HEAT PUMP SHALL MEET OR EXCEED THE EFFICIENCY SPECIFICATIONS IN THE ATTACHED EVERSOURCE2021 HVAC INCENTIVE APPLICATION. IF THE AIR TO AIR HEAT PUMP IS RECOMMENDED, IT SHALL BE PROVIDED BY A PROPANE UNIT.



**International Beams Assembly IB.P60.1**  
**One-Hour Fire Resistance Rated Floor/Ceiling Assembly**  
 This fire resistance design is listed in accordance with the ASTM E119 and CAN/ULC S101  
 Min. 9-1/2 inches (241 mm) Deep: IB800 or WI 80, and IB900 I-Joists  
 Manufactured at the Pohénegamook, Quebec Plant (Mill #1033)




**A. BASIC ASSEMBLIES**

- 1) Floor Topping (Optional): Varies.
- 2) Floor Sheathing: Min. 5/8-inch (16-mm) T&G Wood Structural Panel when topping is used and the joist spacing is 19.2 inches (488 mm) or less. Otherwise, Min. 23/32-inch (18-mm) T&G Wood Structural Panel must be used. The sheets shall be installed with their long edge perpendicular to I-joists with end joints centered over the top flange of I-joists and staggered. Floor sheathing must be installed per code requirements.
- 3) Insulation: Min. 1-1/2-inch (38-mm) Mineral Wool Insulation Batts (nominal 2.5 pcf) friction fit between I-joist flanges.
- 4) Structural Members: Min. 9-1/2 inches (241 mm) Deep I-Joists. Max. 24 inches (610 mm) on center spacing. Min. flange dimensions of 1-1/2 inches (38 mm) thick by 3-1/2 inches (89 mm) wide. Min. web thickness of 3/8 inch (9.5 mm).
- 5) Resilient Channels: Min. 25 Gauge Galvanized Resilient Channels. Attached perpendicular to the bottom flange of the I-joist with 1-5/8 inch (41-mm) Type W drywall screws. Channels are spaced a max. of 16 inches (406 mm) on center, are doubled at each base layer wallboard end joint, and extend to the next joist beyond each joint.
- 6) Ceiling: One layer of 5/8-inch (16-mm) Type C Gypsum Wallboard. Installed with long dimension perpendicular to resilient channels and fastened with min. 1-1/8-inch (29-mm) Type S drywall screws spaced at 7 inches (178 mm) on center. The end joints of the wallboard must be staggered 48 inches (1219 mm) with those of adjacent sheets. Screws shall be min. 1-1/2 inches (38 mm) from board edges and 3/4 inch (19 mm) from board ends.
  - a) Finish: The face layer joints must be covered with tape and coated with joint compound. Screw heads must also be covered with joint compound.

**B. SIMILAR ASSEMBLIES**

- 1) Intertek Listing IBI-MWP 80-01, and 2010 NBCC Table A-9.10.3.1.B Assemblies F8, F10, F14, and F20.




| LEGEND |  |
|--------|--|
| Ⓢ      | SWITCH   |
| Ⓢ 3    | SWITCH (3-WAY)   |
| Ⓢ D    | SWITCH (3-WAY - WITH DIMMER)                                       |
| Ⓢ      | DUPLEX RECEPTACLE  |
| Ⓢ GFI  | DUPLEX RECEPTACLE (GROUND FAULT)                                   |
| Ⓢ R    | LED RECESSED FIXTURE   |
| Ⓢ H    | HISTORIC STYLE LED FIXTURE - TBD BY ARCHITECT / HISTORIC COMMITTEE |
| Ⓢ C    | CEILING MOUNTED LED LIGHT FIXTURE                                  |
| Ⓢ L    | LED LIGHT FIXTURE  |
| Ⓢ T    | 2'x4' LED TROFFER LIGHT FIXTURE                                    |
| Ⓢ F    | EXHAUST FAN  |
| Ⓢ E    | LED EMERGENCY LIGHTING - BATTERY                                   |
| Ⓢ FL   | LED FLOOD LIGHTING   |
| Ⓢ S    | SMOKE DETECTOR   |
| Ⓢ EX   | ILLUMINATED EXIT SIGN  |
| Ⓢ F    | FIRE ALARM MANUAL PULL STATION                                     |
| Ⓢ EXT  | FIRE EXTINGUISHER  |

**PROPOSED PHASE ONE & TWO ELECTRICAL / PLUMBING PLAN**

**CONSTRUCTION SET**

|  |                       |
|--|-----------------------|
| <b>RYE TOWN OFFICE</b><br><b>RYE, NH.</b>  |                       |
| <b>PHASE ONE &amp; TWO ELECTRICAL AND PLUMBING PLAN</b><br>SCALE: 3/16"=1'-0"  |                       |
| <br><b>CHARLES HOYT DESIGNS</b><br>Single Style Architecture<br>P.O. BOX 256<br>RYE, NH 03081<br>(603) 431-5310<br>charles@hoytdesigns.com | <b>A11</b><br>12-1-21 |



RYE TOWN OFFICE  
500 WASHINGTON ROAD  
RYE, NH 03870

LIST OF PROJECT PLANS AND DOCUMENTS:

PLAN SET

- S1 - Foundation Plan
- S2 - 1st & 2nd Floor Framing Plan
- S3 - Framing Details
- S4 - Framing
- S5 - Roof Framing Plans
- S6 - General Notes

PREPARED BY:


ROSS ENGINEERING, LLC

Civil/Structural Engineering  
& Surveying  
909 Islington St.  
Portsmouth, NH 03801  
(603) 433-7560


PREPARED FOR:  
CHARLES HOYT DESIGNS  
P.O. BOX 256  
Rye Beach, NH 0371

November 1, 2021







**FOUNDATION PLAN**  
Scale: 3/16"=1'-0"




**SECTION 1**  
Scale: 1"=1'-0"




**SECTION 2**  
Scale: 1"=1'-0"



**SECTION 3**  
Scale: 1"=1'-0"



**BEAM POCKET DETAIL**  
Scale: NTS



**LALLY DETAIL**  
Scale: 1"=1'-0"


**FOOTER SCHEDULE**

|    |  |
|----|--|
| F1 | 4"x4"x10" WITH (4) #4 BARS EA. WAY     |
| F2 | 4 1/2"x2"x10" WITH (4) #4 BARS EA. WAY |


**COLUMN SCHEDULE**

|    |                             |
|----|-----------------------------|
|    | TYPE OF POST                |
| P1 | HSS 4"x4"x4"                |
| P2 | 3 1/2"x5 1/4" VERSALAM POST |
| P3 | 5 1/4"x5 1/4" VERSALAM POST |
| P4 | 7"x7" VERSALAM POST         |
| P5 | 4" LALLY COLUMN             |


ASSURE POSITIVE ATTACHMENT AT ALL POST TO BEAM CONNECTIONS



**TOP PLATE DETAIL**  
Scale: 3"=1'-0"



**BASE PLATE DETAIL**  
Scale: 3"=1'-0"



**HSS COLUMN DETAIL**  
Scale: 1"=1'-0"

**REVISION HISTORY**

| REV | DATE       | DESCRIPTION  | CHK |
|-----|------------|--------------|-----|
| 1   | 11/01/2021 | FOR APPROVAL |     |

**ROSS ENGINEERING, LLC**  
Civil/Structural Engineering & Surveying  
909 Islington St.  
Portsmouth, NH 03801  
(603) 433-7560


**FOUNDATION PLAN**  
**RYE TOWN OFFICE**  
500 WASHINGTON ROAD  
NEW HAMPSHIRE  
RYE

PREPARED FOR:  
CHARLES HOYT  
DESIGNS  
P.O. BOX 256  
RYE BEACH, NH 03871

DESIGNED BY:  
ADH 8-4-2021

DRAFTED BY:  
ADH 8-4-2021


CHECKED BY:  
MGP 8-4-2021



JOB #: 21-043  
SCALE: AS NOTED  
SHEET: OF 6  
DRAWING:

**S1**






**FIRST FLOOR FRAMING PLAN**  
Scale: 3/16"=1'-0"


| FOOTER SCHEDULE |  |
|-----------------|--|
| F1              | 4'x4'x10" WITH (4) #4 BARS EA. WAY     |
| F2              | 4 1/2'x2'x10" WITH (4) #4 BARS EA. WAY |


| COLUMN SCHEDULE |                             |
|-----------------|-----------------------------|
| TYPE OF POST    |                             |
| P1              | HSS 4"x4"x4"                |
| P2              | 3 1/2"x5 1/4" VERSALAM POST |
| P3              | 5 1/4"x5 1/4" VERSALAM POST |
| P4              | 7"x7" VERSALAM POST         |
| P5              | 4" Ø LALLY COLUMN           |



**SECTION A**  
Scale: 1/4"=1'-0"



**SECOND FLOOR FRAMING PLAN**  
Scale: 3/16"=1'-0"



**SECTION B**  
Scale: 1/4"=1'-0"

| REV | DATE       | DESCRIPTION  | CHK |
|-----|------------|--------------|-----|
| 1   | 11/01/2021 | FOR APPROVAL |     |

**ROSS ENGINEERING, LLC**  
Civil/Structural Engineering & Surveying  
909 Islington St.  
Portsmouth, NH 03801  
(603) 433-7560

**PROPOSED FRAMING**  
**RYE TOWN OFFICE**  
500 WASHINGTON ROAD  
NEW HAMPSHIRE  
RYE


PREPARED FOR:  
CHARLES HOYT  
DESIGNS  
P.O. BOX 256  
RYE BEACH, NH 03871  
DESIGNED BY:  
ADH 8-4-2021  
DRAFTED BY:  
ADH 8-4-2021  
CHECKED BY:  
MGP 8-4-2021



JOB #: 21-093  
SCALE: AS NOTED  
SHEET: 2 OF 6  
DRAWING:


**S2**






**SECOND FLOOR AND ROOF SECTION**

Scale: 3/8"=1'-0"




**TYPICAL BUILT-UP HEADER INTERIOR WALL**

Scale: NTS




**TYPICAL BUILT-UP HEADER EXTERIOR WALL**




**I-JOIST TO WALL DETAIL**

Scale: NTS




**SQUASH BLOCK DETAIL**

Scale: NTS




**DETAIL A**

Scale: 1/2"=1'-0"



**DETAIL B**

Scale: 1/2"=1'-0"



| REV | DATE       | DESCRIPTION  | CHK |
|-----|------------|--------------|-----|
| 1   | 11/01/2021 | FOR APPROVAL |     |

**ROSS ENGINEERING, LLC**  
Civil/Structural Engineering & Surveying  
909 Islington St.  
Portsmouth, NH 03801  
(603) 433-7560


**DETAILS**  
**RYE TOWN OFFICE**  
500 WASHINGTON ROAD  
NEW HAMPSHIRE  
RYE

PREPARED FOR:  
CHARLES HOYT  
DESIGNS  
P.O. BOX 256  
RYE BEACH, NH 03871  
DESIGNED BY:  
ADH 8-4-2021  
DRAFTED BY:  
ADH 8-4-2021  
CHECKED BY:  
MGP 8-4-2021




JOB #: 21-093  
SCALE: AS NOTED  
SHEET: 3 OF 6  
DRAWING:


**S3**




**ATTIC FRAMING PLAN**  
Scale: 3/16"=1'-0"




**WALL BLOCK ADDITION**  
Scale: Not to Scale




**SECTION D**  
Scale: 1/2"=1'-0"



**SECTION C**  
Scale: 3/8"=1'-0"



**TYPICAL WALL CORNER**  
Scale: Not to Scale




**CMU WALL CONSTRUCTION**  
Scale: Not to Scale

| REV | DATE       | DESCRIPTION  | CHK |
|-----|------------|--------------|-----|
| 1   | 11/01/2021 | FOR APPROVAL |     |

**ROSS ENGINEERING, LLC**  
Civil/Structural Engineering & Surveying  
909 Islington St.  
Portsmouth, NH 03801  
(603) 433-7560

**PROPOSED FRAMING**  
**RYE TOWN OFFICE**  
500 WASHINGTON ROAD  
NEW HAMPSHIRE  
RYE


PREPARED FOR:  
CHARLES HOYT  
DESIGNS  
P.O. BOX 256  
RYE BEACH, NH 03871  
DESIGNED BY:  
ADH 8-4-2021  
DRAFTED BY:  
ADH 8-4-2021  
CHECKED BY:  
MGP 8-4-2021




JOB #: 21-093  
SCALE: AS NOTED  
SHEET: 4 OF 6  
DRAWING:

**S4**







**ROOF FRAMING PLAN**  
Scale: 3/16"=1'-0"




**SECTION 6**  
Scale: 1/4"=1'-0"



**FLITCH PLATE BEAM DETAIL**  
Scale: 1 1/2"=1'-0"



**FLITCH PLATE BEAM DETAIL**  
Scale: 1 1/2"=1'-0"




**ROOF SUPPORT TRUSS**  
Scale: NTS

| REV | DATE       | DESCRIPTION  | CHK |
|-----|------------|--------------|-----|
| 1   | 11/01/2021 | FOR APPROVAL |     |

**ROSS ENGINEERING, LLC**  
Civil/Structural Engineering & Surveying  
9097 Islington St.  
Portsmouth, NH 03801  
(603) 433-7560

**PROPOSED ROOF FRAMING**  
**RYE TOWN OFFICE**  
500 WASHINGTON ROAD  
NEW HAMPSHIRE  
RYE

PREPARED FOR:  
CHARLES HOYT  
DESIGNS  
P.O. BOX 256  
RYE BEACH, NH 03871  
DESIGNED BY:  
ADH 8-4-2021  
DRAFTED BY:  
ADH 8-4-2021  
CHECKED BY:  
MGP 8-4-2021



JOB #: 21-093  
SCALE: AS NOTED  
SHEET: 5 OF 6  
DRAWING:

**S5**



**GENERAL NOTES:**

**SCOPE OF ENGINEERING SERVICE:**

ROSS ENGINEERING IS ONLY RESPONSIBLE FOR THE STRUCTURAL DESIGN AND ENGINEERING AS SHOWN ON THESE DRAWINGS.

THE INTENT OF THIS DRAWING SET IS TO DEPICT THE STRUCTURAL MEMBERS REQUIRED. SEE ARCHITECTURAL DRAWINGS FOR ADDITIONAL INFORMATION BY CHARLES HOYT DATED 10-27-2021.

**GENERAL:**

1. ALL WORK SHALL CONFORM TO THE FOLLOWING REFERENCE STANDARDS:

- "INTERNATIONAL BUILDING CODE" - 2015 EDITION.
- "MINIMUM DESIGN LOADS FOR BUILDINGS AND OTHER STRUCTURES" - ASCE 7-10.
- "SPECIFICATIONS FOR STRUCTURAL CONCRETE FOR BUILDINGS" - ACI 301-05.
- "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE" - ACI 318-11.
- "NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION" - AF&PA NDS-2005.

2. ALL CONTRACTORS SHALL VERIFY AND COORDINATE ALL DIMENSIONS AND DETAILS RELATED TO THIS PROJECT. DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE PROJECT ENGINEER PRIOR TO PROCEEDING WITH THE AFFECTED WORK. ANY CHANGES OR SUBSTITUTIONS OF MATERIALS OR DETAILS FROM THOSE INDICATED ON THE CONTRACT DOCUMENTS MAY BE MADE ONLY WITH PRIOR APPROVAL OF THE PROJECT ENGINEER.

3. ALL CONTRACTORS SHALL BE RESPONSIBLE FOR ALL CONSTRUCTION MEANS, METHODS, COORDINATION OF OTHER TRADES AND THE TECHNIQUES TO PRODUCE A SOUND AND QUALITY PROJECT. SHORING IS THE RESPONSIBILITY OF THE CONTRACTOR.

4. ALL CONTRACTORS SHALL BE RESPONSIBLE FOR ALL JOB SAFETY DURING CONSTRUCTION INCLUDING BUT NOT LIMITED TO SHEETING, SHORING, AND GUYING STRUCTURES, BARRIERS AND SIGNAGE.

5. ALL DETAILS AND NOTES SHOWN ON THE CONTRACT DOCUMENTS SHALL BE CONSIDERED TYPICAL FOR ALL SIMILAR CONDITIONS EXCEPT WHERE SPECIFICALLY REQUIRED OTHERWISE.

6. NO MAIN FRAMING OR STRUCTURAL MEMBERS ARE TO BE MODIFIED, ALTERED, OR CUT WITHOUT THE APPROVAL OF THE PROJECT ENGINEER.

**STRUCTURAL LOADS:**

- LIVE LOADS
  - PER INTERNATIONAL BUILDING CODE - 2015 EDITION
  - LIVING SPACE.....100 PSF
  - ATTIC SPACE (WITHOUT STORAGE).....20 PSF
- SNOW LOADS
  - PER INTERNATIONAL BUILDING CODE - 2015 EDITION AND MINIMUM DESIGN LOADS FOR BUILDINGS AND OTHER STRUCTURES - ASCE 7-05
  - EXPOSURE.....B
  - GROUND SNOW LOAD.....35 PSF

**FOUNDATIONS:**

- FOUNDATION DESIGN IS BASED ON AN ASSUMED NET ALLOWABLE SOIL BEARING CAPACITY OF 2000 PSF. VARYING CONDITIONS MUST BE BROUGHT TO THE ATTENTION OF THE PROJECT ENGINEER PRIOR TO WORK BEING CARRIED OUT. IT IS RECOMMENDED THAT THE OWNER HIRE A CONSULTANT TO PERFORM SOIL BORINGS AND ASSOCIATED TESTING TO VERIFY THE ASSUMED VALUES. THE CONTRACTOR OR OWNER SHALL ASSUME ALL RESPONSIBILITY IF A GEOTECHNICAL ENGINEER IS NOT RETAINED.
- FOUNDATIONS SHALL BE FOUNDED ON NATURALLY UNDISTURBED SOIL OR CONTROLLED STRUCTURAL FILL HAVING A NET ALLOWABLE BEARING CAPACITY OF 2000 PSF.
- MAINTAIN CONTINUOUS CONTROL OF SURFACE AND SUBSURFACE WATER DURING CONSTRUCTION SUCH THAT FOUNDATION WORK IS IN DRY AND UNDISTURBED SUB-GRADE MATERIAL, AS APPLICABLE.
- ALL FOOTINGS EXPOSED TO FROST TO BE PLACED AT A MINIMUM DEPTH OF 4'-0" BELOW FINISH GRADE. ANY DISCREPANCIES OR ADJUSTMENTS TO THE FOOTING ELEVATIONS TO BE BROUGHT TO THE PROJECT ENGINEER PRIOR TO PLACEMENT OF CONCRETE.
- ALL FOOTINGS SHALL BE CENTERED UNDER SUPPORTED STRUCTURAL MEMBERS UNLESS OTHERWISE NOTED ON THE DRAWINGS.
- BACKFILL THE EXCAVATION WITH APPROVED GRANULAR MATERIAL PLACED IN 6 INCH LIFTS AND COMPACTED TO 95% DENSITY AT OPTIMUM MOISTURE CONTENT, AS DEFINED BY ASTM D1557, METHOD D AFTER BOTTOM OF EXCAVATION HAS BEEN APPROVED BY THE PROJECT ENGINEER.
- BACKFILL SHALL BE PLACED TO EQUAL ELEVATIONS ON BOTH SIDES OF FOUNDATION WALLS. WHERE BACKFILL IS ON ONE SIDE ONLY, WORK SHALL BE SHORED OR HAVE PERMANENT ADJACENT CONSTRUCTION IN PLACE BEFORE BACKFILLING.

**CONCRETE NOTES:**

- CONCRETE WORK SHALL CONFORM TO THE FOLLOWING REFERENCE STANDARDS:
  - "INTERNATIONAL BUILDING CODE" - 2015 EDITION.
  - "SPECIFICATIONS FOR STRUCTURAL CONCRETE FOR BUILDINGS" - ACI 301-05.
  - "COLD WEATHER CONCRETING" - ACI-306.
  - "DETAILING REINFORCING STEEL" - ACI 315-05.
  - "BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE" - ACI 318-11.
  - "BUILDING CODE REQUIREMENTS FOR PLAIN CONCRETE" - ACI 322-05.
  - "FORMWORK" - ACI 341-05.
- COMPRESSIVE STRENGTH OF CONCRETE SHALL BE 4000 PSI AFTER 28 DAYS. WITH A SLUMP SHALL OF 4" TO 6" AND IN ACCORDANCE WITH ASTM C143.
- REINFORCING STEEL SHALL BE IN ACCORDANCE WITH ASTM A615 GRADE 60. EXCEPT TIES AND STIRRUPS MAY BE GRADE 40. WELDED WIRE FABRIC (W.W.F.) SHALL BE SHEETS ONLY, IN ACCORDANCE WITH ASTM A185. LAP TWO SQUARES AT ALL JOINTS AND TIE AT 3'-0" ON CENTER.
- CEMENT MIXTURE FOR CONCRETE SHALL CONTAIN TYPE II CEMENT CONFORMING WITH ASTM-C 150. THE WATER CEMENT RATIO SHALL NOT EXCEED 0.45.
- AGGREGATE SHALL BE SOUND AND CONFORM TO THE PROVISIONS OF ASTM C33. COARSE AGGREGATE SIZE SHALL NOT EXCEED ¾". (NO. 67)
- PLACING OF CONCRETE SHALL BE IN ACCORDANCE WITH ACI 304-05 AND SHALL BE A CONTINUOUS OPERATION AVOIDING ANY HORIZONTAL JOINTS. FORMWORK SHALL BE SMOOTH PLYWOOD FORMS FOR EXPOSED SLABS OR VERTICAL SURFACES. BOARD FORMS FOR FOOTINGS OR UNEXPOSED CONCRETE SURFACES. NO EARTH FORMS SHALL BE PERMITTED. ALL CONCRETE SHALL BE VIBRATED.
- PLACE REINFORCING USING STANDARD BAR SUPPORTS TO PROVIDE PROPER CLEARANCE AND PREVENT DISPLACEMENT DURING CONCRETE OPERATIONS. LAP CONTINUOUS BARS 40 DIAMETERS.
- REINFORCING BARS SHALL BE PLACED IN ACCORDANCE WITH THE LATEST EDITION OF THE CRSI "RECOMMENDED PRACTICE FOR PLACING REINFORCING BARS".
- PROPERLY BRACE AND SHORE FORMWORK TO MAINTAIN ALIGNMENT AND TOLERANCES IN ACCORDANCE WITH ACI 341-05.

**CONCRETE CONTINUED:**

- PROVIDE TWO #5 BARS EACH SIDE OF ALL OPENINGS IN WALLS AND SLABS. BARS TO EXTEND 24" BEYOND EDGE OF OPENINGS. (FOR SIZE AND LOCATION OF OPENINGS, SEE ARCHITECTURAL, MECHANICAL AND ELECTRICAL DRAWINGS).
- MINIMUM CONCRETE COVER REQUIREMENTS OVER REINFORCING STEEL ARE AS FOLLOWS:
  - FORMED CONCRETE EXPOSED TO EARTH, WEATHER, OR WATER - 2"
  - UNFORMED CONCRETE PLACED AGAINST THE EARTH - 3"
  - UNFORMED CONCRETE PLACED AGAINST VAPOR BARRIER - 2"
  - SLABS ON GRADE - 1" FROM TOP
- DETAILS NOT SHOWN ON DRAWINGS SHALL BE IN ACCORDANCE WITH THE ACI DETAILING MANUAL (ACI 315-05).
- CONTRACTOR TO NOTIFY THE OWNER'S ENGINEER 48 HOURS IN ADVANCE OF CONCRETE PLACEMENT SO THAT THE FORMWORK AND REINFORCING MAY BE INSPECTED PRIOR TO BEING COVERED.
- CONSULT PROJECT OWNER FOR SURFACE FINISHES REQUIRED FOR CONCRETE SLAB.
- UNDERSLAB VAPOR BARRIER SHALL BE AS MANUFACTURED BY STEGO INDUSTRIES OR EQUAL CONSISTING OF 10 MIL TEGO WRAP VAPOR BARRIER SEAMS SHALL BE OVERLAPPED A MINIMUM OF 6" AND TAPED WITH STEGO VAPOR BARRIER TAPE OR EQUAL AS REQ'D.
- QUALITY CONTROL SPECIFICATIONS ARE AS FOLLOWS:
  - CONTRACTOR SHALL MAKE PROVISIONS TO HAVE FOUR CYLINDERS CAST FOR EACH 50 CUBIC YARDS OR FOR ANY ONE DAYS OPERATION.
  - TESTING LABORATORY SHALL BE RESPONSIBLE FOR MAKING AND CURING SPECIMENS IN CONFORMANCE TO ASTM C31 AND TESTING SPECIMENS IN ACCORDANCE WITH ASTM C24.
  - ALL TESTING ASSOCIATED WITH CONCRETE SHALL BE IN ACCORDANCE WITH CHAPTER 17 OF "INTERNATIONAL BUILDING CODE" - 2004 EDITION.
  - THE COSTS OF ALL TESTS AND INSPECTIONS SHALL BE THE RESPONSIBILITY OF THE OWNER.

**WOOD FRAMING:**

- ALL WOOD FRAMING SHALL CONFORM TO THE FOLLOWING REFERENCE STANDARDS:
  - "INTERNATIONAL BUILDING CODE - 2015 EDITION"
  - "NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION" - AF&PA NDS-2005
- ALL FRAMING MEMBERS SHALL BE No.1 / No. 2 OR BETTER SPRUCE-PINE-FIR WITH A MAXIMUM MOISTURE CONTENT OF 19% UNLESS NOTED OTHERWISE.
  - BASE DESIGN VALUES:
  - Fb=875 (1,000 REP) PSI, Fv=70 PSI, E=1,400 KSI
- ALL LUMBER AND PLYWOOD SHALL BE GRADE-STAMPED BY THE APPROPRIATE MANUFACTURER'S ASSOCIATION FOR THE APPROPRIATE USE.
  - ROOF: 1½" SQUARE EDGE PLYWOOD w/ FRAMING CLIPS
  - FLOORS: 2¾" TONGUE & GROOVE PLYWOOD
  - WALLS: 1½" PLYWOOD
- ROOF AND WALL SHEATHING SHALL COMPLY WITH THE FOLLOWING:
  - APA RATED SHEATHING EXPOSURE 1 OR 2
  - ROOF SHEATHING SHALL HAVE A 40/20 SPAN RATING
  - ROOF SHEATHING SHALL HAVE (1) PANEL EDGE CLIP BETWEEN EACH SUPPORT
  - A 1/8" EXPANSION GAP SHALL BE LEFT BETWEEN ALL PANELS AS REQUIRED BY APA
  - SHEETS SHALL BE INSTALLED WITH FACE GRAIN PERPENDICULAR TO SUPPORTING MEMBERS
- ALL WOOD IN CONTACT WITH CONCRETE, MASONRY, OR EARTH SHALL BE PRESSURE TREATED (PT) WITH A CCA-C 0.40 PROCESS.
- ALL FRAMING SHALL BE PLUMB, TRUE, AND ADEQUATELY BRACED SUCH THAT THE STRUCTURE IS RIGID AND BEARS FULLY WITHOUT THE USE OF SHIMS.
- SPIKE TOGETHER ALL FRAMING MEMBERS WHICH ARE BUILT UP WITH 16d NAILS AT 16" O.C. MAX. UNLESS NOTED OTHERWISE. PROVIDE PLYWOOD FILLERS BETWEEN 2x MEMBERS TO MATCH WALL THICKNESS.
- PROVIDE A MINIMUM OF TWO 2x STUDS AT THE END OF ALL BUILT-UP 2x BEAMS AND LVL BEAMS, UNLESS NOTED OTHERWISE.
- CORNERS OF EXTERIOR WALLS SHALL HAVE A MINIMUM OF (3) 2x STUDS.
- PROVIDE SOLID BLOCKING UNDER ALL CONCENTRATED LOADS. PROVIDE CONTINUITY TO TOP OF FOUNDATION WALL OR FOOTING.
- PROVIDE A DOUBLE TOP PLATE FOR ALL EXTERIOR WALLS w/ SPLICES STAGGERED BY 4'-0" MIN.
- NON-STRUCTURAL INTERIOR WALLS SHALL BE CONSTRUCTED w/ 2x4 STUDS.
- ENGINEERED LUMBER PRODUCTS SHALL BE MANUFACTURED BY BOISE CASCADE OR APPROVED EQUAL, INCLUDING ALL I-JOISTS AND LVL'S. ALL BOISE CASCADE PRODUCTS SHALL BE INSTALLED IN ACCORDANCE WITH THE RECOMMENDATIONS AND STANDARD DETAILS AS PUBLISHED BY BOISE CASCADE.
  - BASE DESIGN VALUES:
  - 1¾" WIDE VERSA-LAM BEAMS GRADE 3100 Fb SP
  - Fb=3,100 PSI, Fv=285 PSI, E=2,000 KSI
  - 3½" AND WIDER VERSA-LAM BEAMS GRADE 3100 Fb SP
  - Fb=3,100 PSI, Fv=285 PSI, E=2,000 KSI
  - VERSA-LAM COLUMNS GRADE 3100 Fb SP
  - Fb=3,100 PSI, Fc11=3,000 PSI, E=1,800 KSI
- FASTENERS SHALL COMPLY WITH THE FOLLOWING:
  - NAILS SHALL BE COMMON WIRE NAILS GALVANIZED @ EXPOSED FRAMING
  - BOLTS, NUTS AND WASHERS SHALL BE ASTM A-307, HOT DIP GALVANIZED AT EXTERIOR EXPOSED FRAMING CONFORMING TO ASTM A153
  - METAL CONNECTORS SHALL BE AS MANUFACTURED BY SIMPSON OR APPROVED EQUAL
  - STAINLESS STEEL NAILS FOR ATTACHING EXTERIOR TRIM AND SIDING
  - ALL WOOD MEMBERS TO BE NAILED IN ACCORDANCE WITH THE INTERNATIONAL BUILDING CODE - 2004 EDITION APPENDIX C
- PLYWOOD SHALL BE NAILED AT 6" OC AT ALL JOINTS AND EDGES & AT 10" OC AT OTHER SUPPORTS. PLYWOOD SUB-FLOORS SHALL BE GLUED TO JOISTS, BEFORE NAILING WITH CONSTRUCTION ADHESIVE.
- LIGHTWEIGHT RESIDENTIAL LALLY COLUMNS - 3½" OUTER DIAMETER 16 GAGE STEEL PIPE CONFORMING TO ASTM A513 FILLED WITH CONCRETE HAVING A MINIMUM COMPRESSIVE STRENGTH OF 2000 PSI AT 28 DAYS. (UNLESS OTHERWISE NOTED.)
- PROVIDE DOUBLE JOISTS UNDER PARALLEL PARTITION WALLS AT ALL FLOORS UNLESS OTHERWISE NOTED.
- NEW PRESSURE TREATING PROCESSES REQUIRED FOR WOOD ARE HIGHLY CORROSIVE. SEE NOTE 5. AND MANUFACTURER'S RECOMMENDATIONS FOR FASTENING TO PT WOOD.

**STRUCTURAL STEEL:**

- ALL STEEL FRAMING WORK SHALL CONFORM TO THE FOLLOWING REFERENCE STANDARDS:
  - "INTERNATIONAL BUILDING CODE" - IBC 2015 EDITION.
  - "SPECIFICATIONS FOR STRUCTURAL STEEL BUILDINGS ALLOWABLE STRESS DESIGN AND PLASTIC DESIGN" - AISC-A36 13TH ED.
  - "D.I. STRUCTURAL WELDING CODE / STEEL" - AWS 1998.
- ALL STEEL FRAMING SHALL CONSIST OF THE FOLLOWING:
  - WF AND WT SHAPES - ASTM A992
  - TUBE COLUMNS - ASTM A500 - GRADE B - Fy=46 KSI
  - PIPE COLUMNS - ASTM A53 - GRADE B - TYPE E OR S, SCHEDULE 80
  - ALL OTHER STRUCTURAL SHAPES AND PLATES - ASTM A36
  - BOLTS - CONNECTIONS ASTM A325, ANCHOR BOLTS ASTM A307
  - WELDING ELECTRODES - E70XX SERIES
- SHOP FABRICATE TO THE GREATEST EXTENT POSSIBLE BY WELDING. PROVIDE ALL BEAM COLUMN STIFFENERS, COLUMN CAPS AND BASE PLATES WITH HOLES AS REQUIRED. PROVIDE ALL NECESSARY CONNECTION HARDWARE FOR CONNECTIONS.
- SUBMIT SHOP DRAWINGS FOR ALL STEEL MEMBERS PREPARED FROM FIELD DIMENSIONS, FOR APPROVAL BEFORE PROCEEDING WITH FABRICATION. CONNECTIONS SHALL BE DESIGNED AND STAMPED BY AN ENGINEER REGISTERED IN THE STATE OF NEW HAMPSHIRE AND SUBMITTED TO SER PRIOR TO FABRICATION. CONNECTIONS SHALL BE BOLTED WITH A325-N BOLTS.
- PROVIDE ALL ANCHOR BOLTS, LEVELING PLATES, AND ALL NECESSARY HARDWARE TO ERECT THE STEEL PLUMB, LEVEL AND SQUARE. PROVIDE TEMPORARY BRACING UNTIL ROOF AND PERMANENT BRACING IS IN PLACE.
- CONTRACTOR SHALL FIELD TOUCH UP ALL ABRASIONS, BURNS AND SIMILAR DEFECTS IN PAINT OF ALL STRUCTURAL STEEL.
- QUALITY CONTROL SPECIFICATIONS ARE AS FOLLOWS:
  - PROVIDE SERVICE OF INDEPENDENT TESTING LABORATORY FOR THE FOLLOWING:
    - VISUAL INSPECTION OF FILLET WELDS.
    - INSPECTION OF BOLT INSTALLATION AND BOLT TENSION.
  - ALL TESTING ASSOCIATED WITH STRUCTURAL STEEL SHALL BE IN ACCORDANCE WITH THE APPROPRIATE SECTION OF IBC 2015.
  - THE COSTS OF ALL TESTS AND INSPECTIONS SHALL BE THE RESPONSIBILITY OF THE OWNER.
- ERECTION NOTES: TOUCH-UP AND REPAIR FOR METAL-COATED SURFACES, CLEAN WELDS, BOLTED CONNECTIONS AND ABRADED AREAS; APPLY ORGANIC ZINC REPAIR PAINT COMPLYING WITH REQUIREMENTS OF ASTM A780. GALVANIZING REPAIR PAINT SHALL HAVE 65% ZINC BY WEIGHT. THICKNESS OF APPLIED GALVANIZING REPAIR PAINT SHALL NOT BE LESS THAN COATING THICKNESS REQUIRED BY ASTM A123 OR A153 AS APPLICABLE.
- ALL WELDING SHALL BE PERFORMED BY AWS-CERTIFIED WELDERS.
- SHOP FABRICATE TO THE GREATEST EXTENT POSSIBLE BY WELDING. PROVIDE ALL BEAM COLUMN CAPS AND BASES WITH HOLES AS REQUIRED. PROVIDE ALL NECESSARY CONNECTION HARDWARE FOR CONNECTIONS.
- PAINT - NON-GALVANIZED STEEL SHALL RECEIVE APPROVED PRIMER - 2 MILS THICK, ALL STRUCTURAL STEEL SHALL BE SHOP PAINTED WITH ONE COAT OF SHERWIN WILLIAMS STRUCTURAL STEEL PRIMER, GRAY (PRODUCT NUMBER B50AV11).

| REV | DATE       | DESCRIPTION  | CHK |
|-----|------------|--------------|-----|
| 1   | 11/01/2021 | FOR APPROVAL |     |
|     |            |              |     |
|     |            |              |     |
|     |            |              |     |
|     |            |              |     |

**ROSS ENGINEERING, LLC**  
 Civil/Structural Engineering & Surveying  
 909 Islington St.  
 Portsmouth, NH 03801  
 (603) 433-7560


**NOTES**  
**RYE TOWN OFFICE**  
 500 WASHINGTON ROAD  
 NEW HAMPSHIRE  
 RYE

PREPARED FOR:  
 CHARLES HOYT  
 DESIGNS  
 P.O. BOX 256  
 RYE BEACH, NH 03871

DESIGNED BY:  
 ADH 8-4-2021

DRAFTED BY:  
 ADH 8-4-2021


CHECKED BY:  
 MGP 8-4-2021



JOB #: 21-093  
 SCALE: AS NOTED  
 SHEET: 5 OF 6  
 DRAWING:

**S6**





**NOTES:**



- 1. TEST FOR ASBESTOS AND LEAD PRIOR TO DEMOLITION, OR SET DEBRIS ASIDE TO BE TESTED BEFORE DISPOSAL.
- 4. CUT OFF ALL ELECTRICAL SERVICE EXCEPT IN WALL(S) NOT DESIGNATED FOR DEMOLITION, PRIOR TO THE START OF WORK.

**DEMO 1 - BY RYE PUBLIC WORKS FOR THE PURPOSE OF VERIFYING EXISTING STRUCTURAL CONDITIONS**

**DEMO 2 - BY FOR PHASE ONE AND TWO WORK BY CONTRACTOR OR BY RYE PUBLIC WORKS - IF BY RYE PUBLIC WORKS, WORK WILL BE COORDINATED BY CHARLES HOYT DESIGNS**


**DEMOLITION PLAN**

|                         |  |   |
|-------------------------|--|---|
| <b>CONSTRUCTION SET</b> | <b>RYE TOWN OFFICE</b><br>RYE, NH.   | DEMOLITION FLOOR PLAN<br>SCALE: 3/16"=1'-0" |
|                         | <b>CHARLES HOYT DESIGNS</b><br><small>Single Style Architecture</small><br>P.O. BOX 256<br>RYE, NH 03345<br>(603) 431-5310<br><a href="mailto:charles@hoyt-designs.com">charles@hoyt-designs.com</a> | <b>D1</b>                                   |





DEMOLITION ELEVATIONS

CONSTRUCTION SET


|  |                                     |   |
|--|-------------------------------------|---|
|  <p><b>CHARLES HOYT DESIGNS</b><br/>Shingle Style Architecture<br/>P.O. BOX 256<br/>Rye, NH 03071<br/>(603) 431-5310<br/>charlesoyt@charlesoytdesigns@hotmail.com</p> | <p>RYE TOWN OFFICE<br/>RYE, NH.</p> | <p>DEMOLITION ELEVATIONS<br/>SCALE: 3/16"=1'-0"</p> |
|  | <p>12-1-21</p>                      | <p>D2</p>   |






DEMOLITION ELEVATIONS


CONSTRUCTION SET

|   |  |   |
|---|--|---|
|  <p><b>CHARLES HOYT DESIGNS</b><br/>Shingle Style Architecture<br/>P.O. BOX 256<br/>Rye, NH 03071<br/>(603) 431-5310<br/>charlesoyt@charoytdesigns@hotmail.com</p> | <p><b>RYE TOWN OFFICE</b><br/>RYE, NH.</p> | <p>DEMOLITION ELEVATIONS<br/>SCALE: 3/16"=1'-0"</p> |
|   | <p>12-1-21</p>                             | <p><b>D3</b></p>                                    |



EXISTING PLAN

CONSTRUCTION SET



RYE TOWN OFFICE  
RYE, NH.



EXISTING PLAN  
SCALE: 3/16"=1'-0"

12-1-21

E1

P.O. BOX 256  
Rye, NH 03071  
(603) 431-5310  
charles@hoymdesigns@hotmail.com






EXISTING ELEVATIONS

CONSTRUCTION SET

|  |                                     |   |
|--|-------------------------------------|---|
| <p>CHARLES<br/>HOYT<br/>DESIGNS<br/>Shingle Style Architecture<br/>P.O. BOX 256<br/>Rye, NH 03071<br/>(603) 431-5310<br/>charlesoyt@charoytdesigns@hotmail.com</p> | <p>RYE TOWN OFFICE<br/>RYE, NH.</p> | <p>EXISTING ELEVATIONS<br/>SCALE: 3/16"=1'-0"</p> |
|  | <p>12-1-21</p>                      | <p>E2</p>   |






REAR



RIGHT

EXISTING ELEVATIONS

CONSTRUCTION SET

|  |                                     |   |
|--|-------------------------------------|---|
|  <p><b>CHARLES HOYT DESIGNS</b><br/>Shingle Style Architecture<br/>P.O. BOX 256<br/>Rye, NH 03071<br/>(603) 431-5310<br/>charlesoyt@charlesoytdesigns@hotmail.com</p> | <p>RYE TOWN OFFICE<br/>RYE, NH.</p> | <p>EXISTING ELEVATIONS<br/>SCALE: 3/16"=1'-0"</p> |
|  | <p>12-1-21</p>                      | <p>E3</p>   |